

ACS.CCLP1 B SAFETY ASSESSMENT CRITERIA INITIAL & RE-ASSESSMENT DOMESTIC LPG BOATS

CCLP1 B

INITIAL & RE-ASSESSMENT

Introduction

Tests gas safety competence in core domestic LPG for boats.

CCLP1 B can only be awarded when the Candidate holds CCLP1.

Comprises:

- 3(c). LPG vessel and cylinder location, safety and sizing
- 4. Ventilation
- 5. Installation of pipework and fittings
- 12. Chimney Standards
- 13. Chimney inspection and testing
- 15. Re-establish existing LPG supply and relight appliances.

CBs may adopt Competence and Criteria numbering different to that used in this document.

CB documentation may adopt wording for criteria different to that used in this document, provided the meaning is unaffected.

Range

All LPG fittings on boats.

Pre-requisites

Initial

CCLP1.

Re-assessment

CCLP1 + CCLP1 B.

References and normative documents

MIs.

All relevant documents as listed in the Legislative, Normative & Informative Document List (LINDL), inc.:

- PD 54823:
- BS EN ISO 10239:
- HSL56
- GIUSP.

Where a reference point (REF) is listed in this criteria this is only a guide to where the criteria could be resourced, therefore the REF may not be exhaustive.

ACS.SMB.003.ACRND identifies Normative Documents that should be held by ACs.

Abbreviations

AC. Assessment Centre

CB. Certification Body

B. Boats

I. Initial

MIs. Manufacturer's/manufacturers' instructions

R. Re-assessment

Ref. Reference.

3(b). Cylinder location and safety

KNOWLEDGE AND UNDERSTANDING		REF	I	R	
1. location and safety of cylinders:		N ISO 10239			
(i) installation, location and protection for Propane and Butane cylinders 8.1		8.2 & 8.3	✓		
(ii) construction (inc. ventilation) of compartments, lockers and internal housings		8.2 - 8.5	✓		
		8.6 - 8.7	✓		
2 Requirements for installation of means to test the LPG system for leakage (e.g. bubble		BS EN ISO	✓	✓	
	leak tester/pressure gauge)		10239 4.5		

3(c). Supply pressures - operation and positioning of emergency isolation, flow control and valves for cylinders

KNC	WLEDGE AND UNDERSTANDING		REF	Ι	R
1	Operation and positioning of pressure regulation devices for cylinders		BS EN ISO	√	✓
			10239		
		T = = =	5.5 to 5.7		
2	Over pressure protection & conformity to BS EN 16129:2013	BS EN ISO 10239 5.2 &		✓	✓
		PD 54823:20	16, Section 5		
-	Drocerine requilation devices more than ten years old	DD E4022.20	16 Cootion F	./	./
3	Pressure regulation devices more than ten years old	PD 54823:20	16, Section 5	V	V
4	external manual output pressure regulation devices	BS EN ISO 10	0239 5.4	✓	✓

4. Ventilation

PE	RFORMANCE CRITERIA			REF	Ι	R
1.	calculate free area of a selection of air vents			PD 54823:2016 Annex C or BS EN ISO 10239 Annex B	√	√
2.	identify correct and incorrect types of air vents and grilles e.g.	fly screens		Annex C	✓	✓
3.	identify inadequate ventilation	,		GIUSP	✓	✓
KN	IOWLEDGE AND UNDERSTANDING (these criteria are PC for	or re-asses	sment)	REF	Ι	R
1.	siting of ventilation (hull, windows, decks and ducted) direct to air vents	outside air,	or via series	BS EN ISO 10239 Section 9 PD 54823:2016 Section 13 & Annex C	√	V
2.	Minimum ventilation requirements			23:2016 Annex C & SO 10239 Annex B	✓	√
3.	installation of ventilation grilles and vents	PD 548	23:2016 Secti	on 13 & Annex C	✓	
4	types of grilles and vents			PD 54823:2016 Section 13 & Annex C	√	
5.	additional ventilation e.g. extractor fans, cooker hoods, dryers e			BS 6172 : 2010 14.6	√	
6.	labels and notices including those required for non-room- seale appliances	ed	PD 54823:2016 Se	ection 7 & Annex E	√	✓
7.	New and existing appliances installed in petrol engine s	paces		PD 54823 section 7	√	√
8.	calculating ventilation for closed compartments			PD 54823:2016 Annex C & MI's	✓	✓
9.	calculating ventilation for cupboards and compartments for operassisted flue appliances	n, balanced	and fan	PD 54823:2016 Annex C	✓	√
10	calculating ventilation for combustion air for multi-appliance inst	allations		Annex C	✓	✓
11	requirements for flueless appliances (unflued)			PD 54823:2016 Annex C	✓	
12	12. Requirements and positioning of trunked ventilation into a space containing a gas appliance(s)		BS EN ISO 10239. 7.4.2	✓		
13. location and ventilation for gas cylinder lockers and housings			8.5	✓	✓	
14. protection for low level appliances (gas detection and interlocks)			BS 6172 : 2010 7.6	✓	✓	
15	5. siting of ventilation through engine compartments			BS 54823 Annex C	✓	✓

5. Installation of pipework and fittings. Range of pipe sizes: 4mm to 22mm

PERI	FORMANCE CRITERIA	REF	I	R
1.	join soft copper pipe with appropriate compression fittings, methods and agents	BS EN ISO 10239 6.2.4	√	
KNO	WLEDGE AND UNDERSTANDING	REF	I	R
1.	copper pipe and fittings, standards, suitability and use - hard soldering	BS EN ISO 10239 6.4.1	✓	✓
1a	Wall thickness requirements for solid drawn copper/stainless steel pipework	BS EN ISO	✓	✓
2.	pliable corrugated stainless steel tubing (PCT) and fittings, standards, suitability and use	10239 6.2.1	√	√
3.	jointing copper and stainless steel pipework	BS EN ISO 10239 6.2.4	√	√
4.	restrictions on use of union, compression and capillary fittings	BS EN ISO 10239 6.2.5 6.2.6 6.4.2	✓	✓
4a.	Correct use of self-sealing connections i.e. bayonets	PD 54823:2016 6.2	✓	√
4b	The requirements for shut off valves or solenoid valves and location/s	6.6	✓	✓
5.	sleeve pipework through bulkheads	BS EN ISO 10239 6.5.4 6.5.6 6.5.7	√	
6.	pipework passing through engine compartments	6.2.2 & 6.2.3	✓	
6a	pipework passing through engine compartments prior to May 1999	PD 54823:2016 6.2 (note 4)	√	
7.	precautions and protection when installing pipework	6.5.2 & 6.5.3	✓	✓
8	requirements for pipework when in direct contact with metallic parts of the craft structure	BS EN ISO 10239 6.5.1	✓	√
9	Design guide for pressure drops and pipe sizing exercise	PD 54823:2016 Annex B	✓	✓

12. Chimney / Flueing Standards for appliances

KNO	WLEDGE AND UNDERSTANDING		REF	I	R
1.	open gas flue systems: natural draught:				
(i)					
			PD 54823:	✓	✓
(ii)	(ii) flue requirements, termination positions for open flues before May 1999 (refuelling)		Section 13		
(iii)	(iii) flueing appliances installed in boats (after May 1999)		PD 54823:	✓	
			Section 13		
(iv)	specific flue heights and termination positions for open and closed flu	es	BS EN ISO	✓	
			10239:2014		
()		DD 54022	Section 13		
(v)	risk assessments when replacing existing open flue water heaters		:2016 Section 7	✓	√
(vi)	i) Requirements for non room-sealed refrigerators PD 54823:		2016 Section 7	✓	✓
2.	room sealed: natural draught:				
(i)	room sealed flue construction		BS EN ISO	✓	✓
			10239		
			Section 13		
			& MI's		
(ii)	restrictions for room sealed termination positions (PD 54823 and BS	EN ISO	BS EN ISO	✓	✓
	10239)		10239		
			13.6		
(iii)	requirements and restrictions for room sealed appliances termination	1	BS EN ISO	✓	✓
	positions /appliances		10239 -		
			IGE/G/6 and MIs		
(iv)	room sealed flue terminal guards		13.7	✓	✓

13. Flue testing

KN	OWLEDGE AND UNDERSTANDING	REF	I	R
1.	open flue testing procedures PD 54	PD 54823:2016 Annex F		
2. procedures if flue shows signs of spillage		GIUSP	✓	

15. Re-establish existing gas supply and relight appliances

PER	FORMANCE CRITERIA		REF	I	R
1.	 check appliances are designed for a marine environment, CE marked and are of correct type 		BS EN ISO 10239 7.1	✓	
KN	DWLEDGE AND UNDERSTANDING		REF	I	R
1. adjacent structures in contact with any gas appliance		PD 54823 Section 7	√	√	
2	2 combustible materials adjacent to appliances that may be subject to a temperature		BS EN ISO 10239 7.6	√	✓
3 Proximity and flammability of materials to cooking appliances are found MI's & should conform to ISO 9094		BS EN ISO 10239 7. 10 & M's	✓	√	
4.	information for users		PD 5482 Section 12	√	√
5.	cooking appliance restrictions when used with integral LPG cartridges		D 54823:2016 Annex A & S EN ISO 10239 Innex D		√
6.	Commissioning and maintenance tests	•	PD 54823 Section 14	✓	✓