

ACS.CoNGLP1 RPH SAFETY ASSESSMENT CRITERIA INITIAL & RE-ASSESSMENT DOMESTIC NATURAL GAS TO LPG RESIDENTIAL PARK HOMES

CoNGLP1 RPH

INITIAL & RE-ASSESSMENT

Introduction

Comprises:

- 3(b). LPG supply pressures. Operation of and positioning of emergency isolation, flow control and valves.
- 3(c). LPG cylinder and vessel location, safety and sizing
- 4. Ventilation for appliances
- 5. Installation of pipework and fittings
- 15. Re-establish existing LPG supply and relight appliances.

CoNGLP1 RPH can only be awarded when the Candidate holds CoNGLP1.

CBs may adopt Competence and Criteria numbering different to that used in this document.

CB documentation may adopt wording for criteria different to that used in this document, provided the meaning is unaffected.

Range

All LPG fittings in RPHs.

Pre-requisites

Initial

CoNGLP1.

Re-assessment

CoNGLP1 + CoNGLP1 RPH.

References and normative documents

MIs.

All relevant documents as listed in the Legislative, Normative & Informative Document List (LINDL), inc.:

- HSL56
- GIUSP.
- BS 3632:2015

The References (REF) where indicated are only a guide to where the criteria can be resourced and therefore the REF may not be exhaustive.

ACS.SMB. 003.ACRND identifies Normative Documents that should be held by ACs.

Abbreviations

AC. Assessment Centre CB. Certification Body HP. High pressure I. Initial IP. Intermediate pressure MIs. Manufacturer's/manufacturers' instructions MP. Medium pressure R. Re-assessment Ref. Reference UPSO. Under pressure safety cut-off.

1. Gas safety legislation and Standards

| KNO | OWLEDGE AND UNDERSTANDING | REF | Ι | R |
|-----|--|-----|--------------|--------------|
| 1. | a minimum of two Carbon Monoxide alarms conforming to BE EN 50291-1 | | ✓ | ✓ |
| | shall be installed into a RPH manufactured to BS 3632:2015 | | | |
| 2. | Gas Commissioning Notice requirements in accordance to BS 3632:2015. | | \checkmark | \checkmark |

3(b). LPG supply pressures. Operation and positioning of emergency isolation, flow controls and valves

| KNO | WLEDGE AND UNDERSTANDING | REF | Ι | R |
|-----|---|-----|--------------|---|
| 1. | recognising supply pressures from gas storage vessels: MP stage | | \checkmark | ✓ |
| 2. | operation and positioning of first and second stage regulators | | \checkmark | ✓ |
| 3. | | | | |
| 4. | location requirements for regulators and changeover devices | | ✓ | ✓ |
| 5. | | | | |
| 6. | identifying causes of under-pressure conditions | | \checkmark | |
| 7. | operation, positioning and visible indicators of UPSOs | | ✓ | |
| 8. | re-setting UPSOs | | ✓ | |
| 9. | operation and positioning of limited relief valve | | \checkmark | |
| 10. | advice to consumer on re-setting UPSO | | \checkmark | |
| 11. | | | | |
| 12. | operation and positioning of vapour service shut-off valve | | \checkmark | |

3(c). LPG cylinder and vessel location, safety and sizing

| KNO | KNOWLEDGE AND UNDERSTANDING | | Ι | R |
|-------|---|--|--------------|--------------|
| 1. | cylinders: | | | |
| (i) | installation, location and protection for Propane and Butane cylinders | | ✓ | |
| (ii) | construction (inc. ventilation) for compartments, lockers and internal housings | | ~ | |
| (iii) | safety precautions for storage and use of cylinders | | ✓ | |
| 2. | vessels: | | | |
| (i) | installation | | ✓ | ✓ |
| (ii) | marking of common vessels available for single supply | | ✓ | \checkmark |
| (iii) | location | | \checkmark | \checkmark |

4. Ventilation (for appliances)

| KNC | WLEDGE AND UNDERSTANDING | REF | Ι | R |
|-----|--|------------|--------------|---|
| 1. | calculating combustion ventilation requirements in accordance to BS 3632 – 2015 for non-room sealed appliances | | ~ | ~ |
| 2. | legacy RPH ventilation requirements acceptable to MI's for room sealed & non- room sealed appliances | BS 5440 :2 | ~ | ~ |
| | | | | |
| 5. | restrictions for use of screens to prevent entry of vermin | | \checkmark | |
| 7. | Effects of mechanical extract systems | | \checkmark | ✓ |
| 8. | Effects of Passive Stack ventilation systems in accordance to BS 3632: 2015 | | ✓ | ✓ |

5. Installation of pipework and fittings. Range of pipe sizes: 6 mm to 35 mm

| KNC | WLEDGE AND UNDERSTANDING | REF | Ι | R |
|-----|---|-----|--------------|--------------|
| 1. | jointing and cleaning agents for stainless and galvanised steel pipework | | \checkmark | \checkmark |
| 2. | ventilation for pipework installed within ducts | | ✓ | |
| 3. | locations where LPG pipework is not to be installed | | ✓ | ✓ |
| 4. | galvanised steel pipe and fittings, Standards, suitability and use | | ✓ | |
| 5. | Installation of flexible hoses, tubing, assemblies and their connections: | | | |
| i | allowance for movement | | ✓ | ✓ |
| ii | protection against rodent attack | | \checkmark | \checkmark |

15. Re-establish existing supply and relight appliances

| KNO | WLEDGE AND UNDERSTANDING | REF | Ι | R |
|-----|--------------------------|-----|--------------|--------------|
| 1. | commissioning notices | | \checkmark | \checkmark |